



ONE COAT DASH COVER (OCDC) EWI-065

SAFETY SHEET

According to 1907/2006/EC, Article 31

SECTION 1: IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 PRODUCT IDENTIFIER

Product form:	Powder
Product name:	EWI-060 One Coat Dash Cover (OCDC)
Product code:	EWI-060
Type of product:	Basecoat

1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Application of the substance	This product is used for creating a level surface before rendering.
-------------------------------------	---

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Manufacturer:	EWI Pro Insulation Systems Ltd Unit 1-2, King Georges Trading Estate, Davis Road, Chessington, England, KT9 1TT 0800 133 7072 info@ewipro.com technical@ewipro.com
----------------------	--

Producer:	KREISEL - Technika Budowlana Sp. z o.o. ul. Szarych Szeregów 23 60-462 Poznań Poland Tel. +48 (0)61 846 79 00 Fax +48 (0)61 846 79 09 poznan@kreisel.pl
------------------	---

1.4 EXTERNAL EMERGENCY CONTACTS

Environment Agency Emergency Hotline:	+44/(0)800 80 70 60
Emergency Services (UK): Emergency	999

SECTION 2: HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

Classification under CLP: STOT SE 3: H335, Eye Dam. 1: H318, Skin Irrit. 2: H315, Skin Sens. 1A: H317

Most important adverse effects:

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

2.2 LABEL ELEMENTS

Label elements:

Hazard statements: H315: Causes skin irritation. H317: May cause an allergic skin reaction. H318: Causes serious eye damage. H335: May cause respiratory irritation.

Hazard pictograms:

GHS05: Corrosion, GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children. P261: Avoid breathing dust. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection. P302+P352: IF ON SKIN: Wash with plenty of water. P332+P313: If skin irritation occurs. Seek medical advice/attention. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P315: Seek immediate medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse. P501: Dispose of contents/container to appropriate waste collection point.

2.3 OTHER HAZARDS

This product is not identified as a PBT/vPvB substance.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1 SUBSTANCE

This product is a mixture.

3.2 MIXTURE

Description: Mixture of inorganic binders, fillers and nonhazardous additions

Dangerous components:

CAS: 1305-62-0 EINECS: 215-137-3 Reg.nr.: 01-2119475151-45	Calcium dihydroxide Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	10-25%
CAS: 65997-15-1 EINECS: 266-043-4 Reg.nr.: 02-2119682167-31	Portland cement clinker Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	2.5-10%
CAS: 14808-60-7 EINECS: 238-878-4 Reg.nr.:*	Silicon dioxide (quartz, <1% RCS) Substance with a community workplace exposure limit	2.5-10%

Other components:

CAS: 1317-65-3 EINECS: 215-279-6 Reg.nr.: -	Limestone (Calcium carbonate)	50-100%
---	-------------------------------	---------

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES

Skin contact: Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

Eye contact: Rinse the eye with running water for 15 minutes. Do not rub eyes, as additional cornea damage is possible by mechanical stress. Contact a specialist of occupational medicine or an eye specialist.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Get medical attention if any discomfort continues.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If symptoms develop, seek medical attention.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Immediate / special treatment: Eye bathing equipment should be available on the premises.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

Extinguishing media: The mixture is fire resistant in both delivery condition and mixed condition. In the event of a fire, the mixture will

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Exposure hazards: This product is neither explosive nor flammable, and non-oxidizing with other materials. Dust formations react alkaline with water and can cause a fire risk.

5.3 ADVICE FOR FIRE-FIGHTERS

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Personal precautions: Avoid formation of dust. Avoid inhalation, eye and skin contact. If appropriate, reference must be made to

6.2 ENVIRONMENTAL PRECAUTIONS

Environmental precautions: Do not discharge into drains or rivers.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4 REFERENCE TO OTHER SECTIONS

Reference to other sections: Refer to section 8 of SDS.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of dust in the air.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage conditions: Store in a cool, well-ventilated area. Keep the container tightly closed.

7.3 SPECIFIC END USE(S)

Specific end use(s): No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Ingredients with limit values that require monitoring at the workplace:		
65997-15-1 Portland cement clinker		
WEL (Great Britain)	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust	
AGW (Germany)	Long-term value: 5 E mg/ m ³ DFG	
14808-60-7 Silicon dioxide (quartz, <1% RCS)		
WEL (Great Britain)	Long-term value: 5 mg/m ³	
IOELV (EU)	Long-term value: 5 mg/m ³	
1305-62-0 Calcium dihydroxide		
WEL (Great Britain)	Short-term value: 4* mg/m ³ Long-term value: 5.1* mg/m ³ *Respirable fraction	
IOELV (EU)	Short-term value: 4mg/m ³ Long-term value: 1mg/m ³	
AGW (Germany)	Long-term value: 1E mg/m ³ 2(l);Y,EU,DFG	
REACH (Germany)	Short-term value: 4 A mg/m ³ Long-term value: 1A mg/m ³	
TRGS 900 (Germany)	Long-term value: 1 E mg/m ³ Y	
DNELs		
1305-62-0 Calcium dihydroxide		
Inhalation	DNEL (8h) DNEL (15min.)	1 mg/m ³ (Workers) 4 mg/m ³ (Workers)
Additional Occupational Exposure Limit Values for possible hazards		
Components with general dust limit		
MAK D (TRGS 900) (PL)	Short-term value: 2.5 A 20 E mg/m ³ Long-term value: 1.25 A 10 E mg/m ³ A - IFA 6068 (2003) E - IFA 7284 (2003) Germany	

A - Alveoles passing particles E - Respirable particles (DIN EN 481)

8.2 EXPOSURE CONTROLS

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is by hand.

Skin protection: Protective clothing.

Environmental: No data available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

State: Powder

Colour: Light Grey

Odour: Odourless

Evaporation rate: Not applicable.

Oxidising: Not applicable.

Solubility in water: Slightly Soluble

Viscosity: Not applicable.

Viscosity test method: Not applicable.

Boiling point/range°C: 102 -105°C

Melting point/range°C: >1300 °C.

Flammability limits %:

lower: Not applicable.

upper: Not applicable.

Flash point°C: Not applicable.

Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: Not applicable.

Vapour pressure: Not applicable.

Relative density: Not applicable.

pH: >11 Saturated aqueous solution.

9.2 OTHER INFORMATION

Other Information: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

Reactivity: No dangerous reactions known.

10.2. CHEMICAL STABILITY

Chemical stability: The product is stable as long as it is stored properly and kept dry.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

Hazardous reactions: No dangerous reactions known.

10.4 CONDITIONS TO AVOID

Conditions to avoid: No further relevant information available.

10.5 INCOMPATIBLE MATERIALS

Materials to avoid: No further relevant information available.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

Haz. decomp. products: No dangerous decomposition products known

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

The product was not investigated. The statement is derived from the properties of the single components.

Acute toxicity:

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification		
1317-65-3 Limestone (Calcium carbonate)		
Oral	LC50	6450 mg/kg (Rat) (RTECS Data)
65997-15-1 Portland cement clinker		
Oral	LD50	>2000 mg/kg (Mouse) In animal studies with cement dust no acute toxicity was observed. On the basis of the available data, the classification criteria are not fulfilled.
Dermal	LD0 (no lethality)	2000 mg/kg (Rabbit) (Limit test 24h [4]) On the basis of the available data, the classification criteria are not fulfilled.
Inhalation	LD0 (no lethality)	5 mg/m ³ (Rat) (Limit test [10]) On the basis of the available data, the classification criteria are not fulfilled.
1305-62-0 Calcium dihydroxide		
Oral	LD50	7340 mg/kg (Rat) (OECD 425)
Dermal	LD50	>2500 mg/kg (Rabbit) (OECD 402) >2500 mg/kg (Rabbit) (OECD 402)

SYMPTOMS / ROUTES OF EXPOSURE

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: No data available.

SECTION 12: ECOLOGICAL INFORMATION

12.1 TOXICITY

Aquatic toxicity	
1317-65-3 Limestone (Calcium carbonate)	
LC50 (96h)	>100 mg/l (Rainbow trout - <i>oncorhynchus mykiss</i>) (OECD 203)
LC50 (48h)	>100 mg/l (Water flea - <i>daphnia magna</i>) (OECD 202)
EC50	>14 mg/l (Algae - <i>desmodesmus subspicatus</i>) (OECD 201) >1000 mg/l (Activated sewage sludge) (OECD 209)
65997-15-1 Portland cement clinker	
LC50	- mg/l (Water flea - <i>daphnia magna</i>) (low effect [6,8]) - mg/l (Algae - <i>selenastrum coli</i>) (low effect [7,8]) - mg/l (Sediments) (low effect [9])
1305-62-0 Calcium dihydroxide	
LC50 (96h seawater)	457 mg/l (Fish) 158 mg/l (Invertebrate)
LC50 (96h freshwater)	33.884 mg/l (African catfish - <i>clarias gariepinus</i>) 50.6 mg/l (Fish)
EC50 (48h)	49.1 mg/l (Invertebrate)
EC50 (72h)	184.57 mg/l (Algae)

12.2 PERSISTENCE AND DEGRADABILITY

The product is not removable from water by biological cleaning process.

12.3 BIOACCUMULATIVE POTENTIAL

Does not accumulate in organisms.

12.4 MOBILITY IN SOIL

Slightly soluble

Ecotoxicological effects:

Only by increasing the pH value during application of large quantities.

1305-62-0 Calcium dihydroxide	
NOEC (72h) NOEC (14d) NOEC (21d) NOEC (96h) EC10/LC10 (NOEC)	48 mg/l (Algae) 32 mg/l (Invertebrate) 1080 mg/kg (General plants) 56 mg/l (Guppy - poecilia reticulata) 12000 mg/kg (Soil microorganisms) 2000 mg/kg (Soil macroorganisms)

Behaviour in sewage processing plants:

Remark:

Ecotoxicological tests with Portland cement on *Daphnia magna* (US EPA, 1994a, see Section 16 References [6]) and *Selenastrum Coli* (US EPA, 1993, see section 16 literature [7]) have shown little toxicological effect. Therefore, the LC50 and EC50 values could not be determined, see section 16 literature [8]. There were also no toxic effects on sediments found, see section 16 literature [9]. The addition of large quantities of cement in water can cause a pH increase and thus can be toxic to aquatic life.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 RESULTS OF PBT AND vPvB ASSESSMENT

PBT identification: This product is not identified as a PBT/vPvB substance

12.6 OTHER ADVERSE EFFECTS

No further relevant information available.

Literature

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal operations: Transfer to a suitable container and arrange for collection by a specialised disposal company.

Recovery operations: No information available.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14: TRANSPORT INFORMATION

14.1 UN NUMBER

ADR, ADN, IMDG, IATA VOID

14.2 UN PROPER SHIPPING NAME

ADR, ADN, IMDG, IATA VOID

14.3 TRANSPORT HAZARD CLASS(ES)

ADR, ADN, IMDG, IATA VOID

14.4 PACKING GROUP

ADR, IMDG, IATA VOID

14.5 ENVIRONMENTAL HAZARDS

Marine pollutant: No

Environmentally hazardous:

No Marine pollutant: No 14.6.

SPECIAL PRECAUTIONS FOR USER

Special precautions: No special precautions.

SECTION 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH, AND ENVIRONMENTAL REGULATIONS/ LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

Specific regulations: Not applicable.

15.2 CHEMICAL SAFETY ASSESSMENT

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION 16: OTHER INFORMATION

Other information: According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 * indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3:

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



EWIPRO

Render Systems



Address:

Unit 1-2 King George's Trading Estate,
Davis Road,
Chessington,
England,
KT9 1TT

Email:

info@ewipro.com

Phone:

0800 133 7072



EWIPRO



www.ewipro.com