

PRO-600

FINO PRIMER

PRODUCT DATA SHEET

PRO-600 FINO Primer is a ready-to-use polymer-based primer designed to prepare absorbent substrates before the application of compatible FINO microcement products. It helps regulate surface absorbency, consolidate the substrate and promote adhesion between subsequent layers.

Intended Uses

PRO-600 FINO Primer is suitable for absorbent and porous substrates including concrete, masonry, cementitious surfaces, gypsum plaster, plasterboard, screeds and other suitable mineral backgrounds.



Technical Specification

Composition

Polymers and additives

Colour

Colourless when dry

Consumption

≥ 0.05 l/m²

Application and setting temperature

3°C to 35°C

pH

Approx. 7

Drying Time

Approx. 2 hours (temp. +20°C)

Unit Quantity

5 Litre Jerry Can

Please note: These figures may vary based on the substrate and application method.

Please see the reverse of this page for directions for use.

Directions for use

Substrate Preparation

Substrates must be sound, stable, clean and dry. Remove dust, grease, oils, paint residues, loose material and any other contaminants that may affect adhesion. Repair any surface defects before priming and allow repaired areas to dry fully before application.

Product Preparation

PRO-600 FINO Primer is supplied ready to use. Stir thoroughly before application to ensure an even consistency. Do not dilute or mix with other materials.

Application

Apply an even coat using a brush, roller or suitable spray equipment. Avoid excessive application or pooling. Allow the primer to dry fully before applying subsequent compatible materials.

typical consumption is $\geq 0.05 \text{ L/m}^2$. Drying time is approximately 2 hours at +20°C, depending on substrate absorbency, temperature, humidity and site conditions.

Application Conditions

Apply at temperatures between +3°C and +35°C. Protect the surface from frost, rain, excessive heat and strong winds during application and drying.

Clean-up

Clean tools and application equipment with water immediately after use, before the product has dried.

Packaging & Storage

Store PRO-600 FINO Primer in its unopened original packaging in a dry place between +5°C and +25°C. Protect from frost. Shelf life is up to 24 months from the date of manufacture when stored correctly.

Compliance with Standards

Apply PRO-600 FINO Primer in accordance with the project specification and the application requirements of the compatible FINO microcement system.

Safety Measures

Wear suitable gloves, eye protection and protective workwear during handling and application. Avoid contact with skin and eyes. In case of eye contact, rinse thoroughly with clean water and seek medical advice if irritation persists. Follow standard occupational health and safety practices.

General Information

This data sheet replaces all previous editions. The information provided is based on current knowledge and practical experience, and while it has been compiled with care, it is not guaranteed to be accurate, complete or suitable for all applications. It is the responsibility of the user to verify the product's suitability for their specific use case. No legal obligations are established by this document.

Data Sheet Revision Date: 06/10/2026



Address:
Unit 1-2 King George's Trading Estate,
Davis Road,
Chessington,
England,
KT9 1TT

Email:
info@ewipro.com

Phone:
0800 133 7072



EWIPRO



www.ewipro.com