EWIPRO Render Systems

PRO-600

FINO PRIMER

PRODUCT DATA SHEET

PRO-600 FINO Primer is a ready-to-use polymer-based primer designed to prepare absorbent substrates before the application of compatible FINO microcement products.

It helps regulate substrate absorbency, consolidate the surface and promote adhesion between the prepared background and subsequent FINO microcement layers.



Intended Uses

PRO-600 FINO Primer is intended for use as part of the FINO microcement system on suitable absorbent and porous substrates.

It may be applied to properly prepared concrete, masonry, cementitious surfaces, gypsum plaster, plasterboard, screeds and other compatible mineral backgrounds before subsequent FINO microcement layers are installed.

Technical Specification

Composition	Polymers and additives
Quantity Per Unit	1L
Consumption	≥ 0.05L/m²
Coverage Rate	Up to approx. 10m² per 1L jerrycan within the FINO system
Colour	Colourless when dry
pH	Approx. 7
Application Temperature	+3°C to +35°C
Drying Time	Approx. 2 hours at +20°C

Please note: Thickness, consumption, coverage and time figures are indicative only and may vary depending on the substrate, application method and site conditions.

Please see the reverse of this page for directions for use.

Directions for use

Substrate Preparation

The substrate must be sound, stable, clean and dry, and free from dust, grease, oils, paint residues, loose material and other contaminants that may affect adhesion.

Repair surface defects before priming and allow repaired areas to dry fully before applying PRO-600. The substrate should be suitable for the subsequent FINO microcement build-up.

Product Preparation

PRO-600 FINO Primer is supplied ready to use. Stir thoroughly before application to ensure a uniform consistency. Do not dilute with water or mix with other products or additives.

Application

Apply PRO-600 FINO Primer evenly using a brush or roller, ensuring consistent coverage across the prepared substrate. Avoid excessive application and pooling.

Allow the primer to dry fully before applying the subsequent compatible FINO microcement layer.

Typical consumption is ≥0.05L/m² per application. Drying time is approximately 2 hours at +20°C, depending on substrate absorbency, temperature, humidity and site conditions.

Where the relevant FINO system build-up requires more than one primer application, allow each application to dry appropriately before proceeding with the next stage.

Application Conditions

Apply when the air and substrate temperatures are between +3°C and +35°C.

Protect the treated surface from frost, excessive heat and other conditions that may adversely affect drying or subsequent adhesion.

Clean-up

Clean tools and application equipment with clean water immediately after use and before the product dries.

Packaging & Storage

PRO-600 FINO Primer is supplied in 1L jerrycans. Store unopened in the original packaging in dry conditions between +5°C and +25°C. Protect from frost. Shelf life is up to 24 months from the date of manufacture when stored correctly.

Compliance with Standards

N/A

Safety Measures

Wear suitable gloves, eye protection and protective clothing during handling and application.

Avoid contact with the skin and eyes. In the event of eye contact, rinse thoroughly with clean water and seek medical advice if irritation persists. Refer to the latest Safety Data Sheet for full handling, first aid and disposal guidance.

General Information

This data sheet replaces all previous editions. The information provided is based on current knowledge and practical experience, and while it has been compiled with care, it is not guaranteed to be accurate, complete or suitable for all applications. It is the responsibility of the user to verify the product's suitability for their specific use case. No legal obligations are established by this document.

Data Sheet Revision Date: 29/10/2026

Address:
Unit 1-2 King George's Trading Estate,
Davis Road,
Chessington,
England,
KT9 1TT

Email:
info@ewipro.com

Phone:
0800 133 7072